

# **AFTAC**


Air Force Technical Applications Center

NOISE POWER SPECTRAL DENSITY AND COHERENCY ESTIMATES AT SITES IN NEVADA, USA: MINA, EXCELSIOR MOUNTAINS, GABBS VALLEYS, GARFIELD (GAR) SEISMIC STATIONS, AND EAST OF GARFIELD

Bao V. Nguyen and David R. Russell Directorate of Nuclear Treaty Monitoring Research Division

6 JULY 1998

19980921 088



Report AFTAC-TR-98-005 has been reviewed and is approved for publication.

FRANK F. PILOTTE

Director of Nuclear Treaty Monitoring

JOHN T. WIGINGTON III

Colonel, USAF Commander

Addressees: Please notify HQ AFTAC/TTR, 1030 S. Highway A1A, Patrick Air Force Base FL 32925-3002, if there is a change in your mailing address (including an individual no longer employed by your organization) or if your organization no longer wishes to be included in the distribution of future reports of this nature.

#### REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson David Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

David Highway, Suite 1204, Arlington, VA 2220			
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE 6 July 1998	3. REPORT TYPE AND DATE Technical	S COVERED
4. TITLE AND SUBTITLE Noise Power Spectral Den Nevada, USA: Mina, Exce (GAR) Seismic Stations, a	elsior Mountains, Gabbs Va	ates at Sites in	NDING NUMBERS
6. Authors Bao V. Nguyen and Davi	id R. Russell		
7. PERFORMING ORGANIZATION N			REFORMING ORGANIZATION PORT NUMBER
HQ Air Force Technical A 1030 S. Highway A1A Patrick AFB FL 32925-3		(ACIAC/IIA)	TAC-TR-98-005
9. SPONSORING/MONITORING AGE	ENCY NAME(S) AND ADDRESS(ES		ONSORING/MONITORING ENCY REPORT NUMBER
11. SUPPLEMENTARY NOTES			
12a. DISTRIBUTION/AVAILABILITY	STATEMENT	12b. [	ISTRIBUTION CODE
Approved for public relea	ase; distribution unlimite	d.	Α
13. ABSTRACT (Maximum 200 words Noise was analyzed for to units of nanometers (r in the state of Nevada, L GAR seismic stations, a The noise surveys at MI Signal Technical Service GAR seismic stations co posed of two sites were The Southern Methodist of GAR seismic stations the RDAS-200P digitizer REFTEK digitizer. The I	displacement power spenm) <sup>2</sup> /Hertz (Hz) from not JSA, at MINA seismic stations and seismic stations and seismic stations and conducted by the Lawred University (SMU) conducted Signal employed for their noise survey.	ectral density (PSD) in dise time series acquired ations, GABBS Valleys, GAR seismic stations. I GABBS Valleys were dit each location. The nor did at the Excelsior Mourence Livermore National acted the noise surveys the Teledyne Geotech Che LLNL and the SMU 6 Hz are as follows:	ecibels (dB) referenced in 1997, days 216-224, Excelsior Mountains, conducted by the Alliedise survey to the east of tains near MINA comtains near MINA contains near MINA contains the existing locations as 13 seismometer and used the GS-13 and the
13. ABSTRACT (Maximum 200 words Noise was analyzed for to units of nanometers (r in the state of Nevada, L GAR seismic stations, a The noise surveys at MI Signal Technical Service GAR seismic stations co posed of two sites were The Southern Methodist of GAR seismic stations the RDAS-200P digitizer REFTEK digitizer. The I	displacement power spenm) <sup>2</sup> /Hertz (Hz) from noing JSA, at MINA seismic stand nearby to the east of NA seismic stations and es Corp. with four sites and conducted by the Lawred University (SMU) conducted by the Lawred University (SMU) conducted in their noise survey. The PSD results at 1 Hz and (Continued of the conducted of the conducted of the conducted in the conducted in the conducted of th	ectral density (PSD) in dise time series acquired ations, GABBS Valleys, GAR seismic stations. I GABBS Valleys were dit each location. The nor did at the Excelsior Mourence Livermore National acted the noise surveys the Teledyne Geotech Che LLNL and the SMU 6 Hz are as follows:	ecibels (dB) referenced in 1997, days 216-224, Excelsior Mountains, conducted by the Alliedise survey to the east of ntains near MINA complications (LLNL). at the existing locations as-13 seismometer and used the GS-13 and the
13. ABSTRACT (Maximum 200 words Noise was analyzed for to units of nanometers (r in the state of Nevada, L GAR seismic stations, a The noise surveys at MI Signal Technical Service GAR seismic stations co posed of two sites were The Southern Methodist of GAR seismic stations the RDAS-200P digitizer REFTEK digitizer. The Interpretation of Interpretation	displacement power spenm) <sup>2</sup> /Hertz (Hz) from noing JSA, at MINA seismic stand nearby to the east of NA seismic stations and es Corp. with four sites and conducted by the Lawred University (SMU) conducted by the Lawred University (SMU) conducted in their noise survey. The PSD results at 1 Hz and (Continued of the conducted of the conducted of the conducted in the conducted in the conducted of th	ectral density (PSD) in dise time series acquired ations, GABBS Valleys GAR seismic stations. I GABBS Valleys were dit each location. The nor did at the Excelsior Mourence Livermore National acted the noise surveys the Teledyne Geotech Che LLNL and the SMU 6 Hz are as follows: n next page)	ecibels (dB) referenced in 1997, days 216-224, Excelsior Mountains, conducted by the Alliedise survey to the east of tains near MINA complications (LLNL). at the existing locations GS-13 seismometer and used the GS-13 and the
13. ABSTRACT (Maximum 200 words Noise was analyzed for to units of nanometers (r in the state of Nevada, L GAR seismic stations, a The noise surveys at MI Signal Technical Service GAR seismic stations co posed of two sites were The Southern Methodist of GAR seismic stations the RDAS-200P digitizer REFTEK digitizer. The I	displacement power spenm) <sup>2</sup> /Hertz (Hz) from noing JSA, at MINA seismic stand nearby to the east of NA seismic stations and es Corp. with four sites and conducted by the Lawred University (SMU) conducted by the Lawred University (SMU) conducted by the Lawred Continued of Contin	ectral density (PSD) in dise time series acquired ations, GABBS Valleys GAR seismic stations. I GABBS Valleys were dit each location. The nor did at the Excelsior Mourence Livermore National acted the noise surveys the Teledyne Geotech Che LLNL and the SMU 6 Hz are as follows: n next page)	ecibels (dB) referenced in 1997, days 216-224, Excelsior Mountains, conducted by the Alliedise survey to the east of ntains near MINA complications (LLNL). at the existing locations as-13 seismometer and used the GS-13 and the

#### Block 13 Con't:

Name	Latitude ( <sup>0</sup> )	Longitude (°)	Displacement Power Spectral Density in dB referred to 1 nm²/Hz (Day/Night)  1 Hz	Standard Deviation (Day/ Night) 1 Hz 6 Hz	Noise RMS Amplitude (nm) (0.8-3.0 Hz)	Noise Surveyed By
MINA, Site 1	38.2758	-118.4710	-2.5/-9.0 -26.7/-32.7	5.4/5.8 6.3/7.6	0.62/0.33	AlliedSignal
MINA, Site 2	38.2796	-118.4740	-5.5/-9.2 -34.7/-40.1	4.3/4.3 11.1/7.5	0.45/0.31	AlliedSignal
MINA, Site 3	38.2736	-118.4660	-0.2/-6.8 -25.6/-32.0	6.2/6.2 8.2/9.7	0.82/0.41	AlliedSignal
MINA, Site 4	38.2735	-118.4750	-4.2/-9.5 -40.5/-45.3	5.3/5.3 6.5/6.5	0.53/0.27	AlliedSignal
GABBS, Site 1	38.6191	-118.2260	-7.2/-0.5 -40.1/-31.2	8.0/8.0 5.0/9.9	0.37/0.78	AlliedSignal
GABBS, Site 2	38.6192	-118.2300	-1.4/-8.5 -34.9/-38.5	4.7/4.7 5.2/5.7	0.72/0.33	AlliedSignal
GABBS, Site 3	38.6240	-118.2280	1.9/1.2 -34.9/-33.4	8.9/8.9 6.2/11.5	1.07/0.94	AlliedSignal
GABBS, Site 4	38.6179	-118.2200	-0.8/-5.9 -36.1/-35.8	6.8/4.3 5.3/6.4	0.77/0.42	AlliedSignal
LLNL, Site 1	38.4387	-118.2139	4.2/-8.2 -31.0/-36.5	8.6/12.4 9.7/14.1	0.51/0.32	LLNL
LLNL, Site 3	38.4208	-118.1900	-9.3/-12.9 -32.0/-37.4	9.9/14.5 9.6/14.8	0.33/0.21	LLNL
LLNL, Site 4	38.4150	-118.2106	-4.5/-5.0 -28.9/-30.7	4.7/4.0 6.4/4.8	0.51/0.48	LLNL
LLNL, Site 6	38.4336	-118.2193	-5.2/-5.7 -30.2/-32.3	4.6/4.2 6.2/5.3	0.54/0.52	LLNL
Excelsior Mountains, Site1	38.279	-118.4734	-2.3/-6.0 -33.9/-39.2	7.1/7.1 7.8/9.8	0.65/0.43	LLNL
Excelsior Mountains, Site2	38.2737	-118.4749	-7.4/-8.8 -39.1/-44.3	4.7/3.2 5.8/5.7	0.36/0.31	LLNL

Name	Latitude (°)	Longitude (°)	Displacement Power Spectral Density in dB referred to 1 nm <sup>2</sup> /Hz (Day/Night)  1 Hz	Standard Deviation (Day/ Night) 1 Hz	Noise RMS Amplitude (nm) (0.8-3.0 Hz)	Noise Surveyed By
GARA0	38.4268	-118.3000	-8.8/-8.9 -31.0/-33.0	3.7/4.4 4.3/4.6	0.33/0.33	SMU
GARB1	38.4240	-118.3063	-9.6/-9.8 -30.2/-32.5	3.1/3.6 5.3/5.0	0.33/0.32	SMU
GARB2A	38.4208	-118.2898	-9.7/-11.1 -33.7/-37.6	2.3/1.8 7.1/2.0	0.28/0.25	SMU
GARB2	38.4258	-118.2908	-10.8/-11.2 -37.3/-39.3	3.3/3.6 3.8/3.9	0.26/0.25	SMU
GARB3	38.4342	-118.3043	-12.6/-12.3 -40.8/-42.3	2.5/3.0 3.8/3.9	0.21/0.21	SMU
GARBL1	38.4502	-118.2933	-13.5/-13.6 -44.1/-46.5	2.2/2.0 3.5/3.7	0.18/0.18	SMU
GARC4	38.4105	-118.2952	-8.8/-10.0 -35.1/-37.6	4.4/4.9 4.9/5.3	0.30/0.27	SMU

These results can be compared with the United States Geological Survey's (USGS's)

New Low and High Noise Models (NLNM and NHNM) which give -18 and 32 dB re nm<sup>2</sup>/

Hz at 1 Hz, respectively.

With respect to mean PSD values at 1 Hz, GABBS Valleys Site 3 is noisiest with daytime and nighttime noise at +1.9 and +1.2 dB, respectively. Furthermore, the noise levels at sites that are much quieter are LLNL Site 3 east of GAR seismic stations with daytime and nighttime noise levels at -9.3 and -12.9 dB, respectively; GARB3 with daytime and nighttime noise levels at -12.6 and -12.3 dB, respectively. The site at GARBL1 is the quietest site in this survey with daytime and nighttime noise levels at -13.5 and -13.6 dB, respectively.

With respect to mean PSD values at 6 Hz, daytime noise at MINA Site 3 is noisiest with a value of -25.6 dB. Furthermore, the noise levels at sites that are much quieter at night

are MINA Site 4 and LLNL Excelsior Mountains Site 2 with nighttime noise levels at -45.3 and -44.3 dB, respectively. The site at GARBL1 is the quietest site in this survey with daytime and nighttime noise levels at -44.1 and -46.5 dB, respectively.

Signal Coherence Spectra: Signal coherence is excellent with most of coherence values near unity at MINA up to about 2 Hz. Beyond 2 Hz, signal coherency is not interpretable. Good signal coherency is found for other sites such as GABBS, GAR, and LLNL sites. Signal coherency is representable and interpretable at these sites.

Noise Coherence Spectra: Noise coherency is good at GAR and LLNL sites; poorer noise coherency is at MINA and GABBS. Noise coherency is representable and interpretable at these sites.

## CONTENTS

	Page
LIST OF FIGURES	vi
LIST OF TABLES	ix
ACKNOWLEDGMENTS	x
ABSTRACT	1
INTRODUCTION	4
PURPOSE	6
INSTRUMENT RESPONSES	
NOISE ANALYSIS	
COMPARISONS	10
COHERENCE ESTIMATES	15
DISCUSSIONS AND CONCLUSIONS	17
Noise Analysis	17
Coherence Analysis	18
REFERENCES	20
APPENDIX A: PLOTS OF DISPLACEMENT POWER SPECTRAL DENSITY .	21
APPENDIX B: PLOTS OF SIGNAL AND NOISE COHERENCE SPECTRA	43
DISTRIBUTION	49

## LIST OF FIGURES

FIG	URE# PAGE
1.	Site locations of noise survey in Nevada, USA, days 216-224, year 1997 4
2.	The normalized velocity and displacement amplitude system responses for the GS13/RDAS-200P and GS13/REFTEK, respectively
За.	Map of noise survey days 216-224 year 1997-upper part-showing PSD values (Day/Night) in dB (re nm²/Hz) at 1 Hz and 6 Hz, respectively
3b.	Map of noise survey days 216-224 year 1997-middle part-showing PSD values (Day/Night) in dB (re nm²/Hz) at 1 Hz and 6 Hz, respectively 12
3c.	Map of noise survey days 216-224 year 1997-lower part-showing PSD values (Day/Night) in dB (re nm²/Hz) at 1 Hz and 6 Hz, respectively
4.	A composite of mean noise levels (day and night) at 1 Hz and 6 Hz for all the sites of this noise survey.
A1.	Daytime mean noise PSD at Mina Site 122
A2.	Nighttime mean noise PSD at Mina Site 1
A3.	Daytime mean noise PSD at Mina Site 2
A4.	Nighttime mean noise PSD at Mina Site 2
A5.	Daytime mean noise PSD at Mina Site 3
A6.	Nighttime mean noise PSD at Mina Site 3
A7.	Daytime mean noise PSD at Mina Site 4
A8.	Nighttime mean noise PSD at Mina Site 4
A9.	Daytime mean noise PSD at Gabbs Site 1
<b>A</b> 10.	Nighttime mean noise PSD at Gabbs Site 1
A11.	Daytime mean noise PSD at Gabbs Site 2
A12.	Nighttime mean noise PSD at Gabbs Site 2
A13.	Daytime mean noise PSD at Gabbs Site 3

FIGU	RE#	PAGE
A14.	Nighttime mean noise PSD at Gabbs Site 3	28
A15.	Daytime mean noise PSD at Gabbs Site 4	29
A16.	Nighttime mean noise PSD at Gabbs Site 4.	29
A17.	Daytime mean noise PSD at LLNL Site 1 (east of GAR).	30
A18.	Nighttime mean noise PSD at LLNL Site 1 (east of GAR)	30
A19.	Daytime mean noise PSD at LLNL Site 3 (east of GAR).	31
A20.	Nighttime mean noise PSD at LLNL Site 3 (east of GAR)	31
A21.	Daytime mean noise PSD at LLNL Site 4 (east of GAR).	32
A22.	Nighttime mean noise PSD at LLNL Site 4 (east of GAR)	32
A23.	Daytime mean noise PSD at LLNL Site 6 (east of GAR).	33
A24.	Nighttime mean noise PSD at LLNL Site 6 (east of GAR)	33
A25.	Daytime mean noise PSD at LLNL Excelsior Mountains Site 1	34
A26.	Nighttime mean noise PSD at LLNL Excelsior Mountains Site 1	34
A27.	Daytime mean noise PSD at LLNL Excelsior Mountains Site 2	35
A28.	Nighttime mean noise PSD at LLNL Excelsior Mountains Site 2	35
A29.	Daytime mean noise PSD at SMU GARA0 seismic station	36
A30.	Nighttime mean noise PSD at SMU GARA0 seismic station.	36
A31.	Daytime mean noise PSD at SMU GARB1 seismic station	37
A32.	Nighttime mean noise PSD at SMU GARB1 seismic station	37
A33.	Daytime mean noise PSD at SMU GARB2 seismic station	38
A34.	Nighttime mean noise PSD at SMU GARB2 seismic station	38
A35.	Daytime mean noise PSD at SMU GARB2A seismic station	39
A36.	Nighttime mean noise PSD at SMU GARB2A seismic station	39

FIGI	JRE#	\GE
A37.	Daytime mean noise PSD at SMU GARB3 seismic station.	. 40
A38.	Nighttime mean noise PSD at SMU GARB3 seismic station	. 40
A39.	Daytime mean noise PSD at SMU GARBL1 seismic station.	. 41
A40.	Nighttime mean noise PSD at SMU GARBL1 seismic station	. 41
A41.	Daytime mean noise PSD at SMU GARC4 seismic station.	. 42
A42.	Nighttime mean noise PSD at SMU GARC4 seismic station	. 42
B1.	(a) Signals (P waves) recorded at MINA sites. (b) Signal correlation functions relative to site 4. (c) Pre-signal noise at four sites. (d) Noise correlation functions relative to site 4. (e-g) Signal and noise coherency of sites 1, 2, and 3, relative to site 4.	. 44
B2.	Spectral multiplications for signals as well as for pre-signal noise of sites 1, 2, and 3, with site 4.	. 44
B3.	(a) Signals (P waves) recorded at GABBS sites. (b) Signal correlation functions relative to site 2. (c) Pre-signal noise at three sites. (d) Noise correlation functions relative to site 2. (e-f) Signal and noise coherency of sites 1 and 4, relative to site 2.	. 45
B4.	Spectral multiplications for signals as well as for pre-signal noise of sites 1 and 4, with site 2.	. 45
B5.	(a) Signals (P waves) recorded at GAR sites. (b) Signal correlation functions relative to site B3. (c) Pre-signal noise at three sites. (d) Noise correlation functions relative to site B3. (e-f) Signal and noise coherency of sites BL1 and C4, relative to site B3.	. 46
B6.	Spectral multiplications for signals as well as for pre-signal noise of sites BL1 and C4 with site B3.	. 46
B7.	(a) Signals (P waves) recorded at LLNL sites. (b) Signal correlation functions relative to site 4. (c) Pre-signal noise at four sites. (d) Noise correlation functions relative to site 4. (e-g) Signal and noise coherency of sites 1, 3, and 6, relative to site 4.	. 47
B8.	Spectral multiplications for signals as well as for pre-signal noise of sites 1, 3, and 6, with site 4.	. 47
B9.	Spatial coherency as function of distance at some representative frequencies for signals (solid) and noise (dashed) at MINA, GABBS, LLNL, and GAB sites	<b>Δ</b> Ω

### LIST OF TABLES

TA	TABLE#		
1	Site Locations of the Noise Survey.	5	
2	General Information	8	
3.	PSD (Day/Night) Comparisons at 1 Hz and 6 Hz.	14	

#### **ACKNOWLEDGMENTS**

Data for MINA and GABBS were provided by the AlliedSignal Technical Services Corp.

Data for GAR were provided by the Southern Methodist University (SMU). Data for the Excelsior Mountains (near MINA) and at sites east of GAR were provided by Lawrence Livermore National Laboratory (LLNL). Dr. Robert Kemerait, Mr. Thomas Kelly, Mr. John Dwyer, and Mr. Jon Creasey of CTI assisted with the information on the data and coordination with the above groups to effectively make the data delivery as fast and as smooth as possible. Ms. Stephanie Fisher provided editorial and administrative reviews.

#### **ABSTRACT**

Noise was analyzed for displacement power spectral density (PSD) in decibels (dB) referenced to units of nanometers (nm)²/Hertz (Hz) from noise time series acquired in 1997, days 216-224, in the state of Nevada, USA, at MINA seismic stations, GABBS Valleys, Excelsior Mountains, GAR seismic stations, and nearby to the east of GAR seismic stations. The noise survey at MINA seismic stations and GABBS Valleys were conducted by the AlliedSignal Technical Services Corp. with four sites at each location. The noise survey to the east of GAR seismic stations composed of four sites and at the Excelsior Mountains near MINA composed of two sites were conducted by the Lawrence Livermore National Laboratory (LLNL). The Southern Methodist University (SMU) conducted the noise surveys at the existing locations of GAR seismic stations. AlliedSignal employed the Teledyne Geotech GS-13 seismometer and the RDAS-200P digitizer for their noise survey. LLNL and SMU used the GS-13 and the REFTEK digitizer. The PSD results at 1 Hz and 6 Hz are as follows:

Name	Latitude (°)	Longitude ( <sup>o</sup> )	Displacement Power Spectral Density in dB referred to 1 nm²/Hz (Day/Night)  1 Hz	Standard Deviation (Day/Night) 1 Hz 6 Hz	Noise RMS Amplitude (nm) (0.8-3.0 Hz)	Noise Surveyed By
MINA, Site 1	38.2758	-118.4710	-2.5/-9.0 -26.7/-32.7	5.4/5.8 6.3/7.6	0.62/0.33	AlliedSignal
MINA, Site 2	38.2796	-118.4740	-5.5/-9.2 -34.7/-40.1	4.3/4.3 11.1/7.5	0.45/0.31	AlliedSignal
MINA, Site 3	38.2736	-118.4660	-0.2/-6.8 -25.6/-32.0	6.2/6.2 8.2/9.7	0.82/0.41	AlliedSignal
MINA, Site 4	38.2735	-118.4750	-4.2/-9.5 -40.5/-45.3	5.3/5.3 6.5/6.5	0.53/0.27	AlliedSignal
GABBS, Site 1	38.6191	-118.2260	-7.2/-0.5 -40.1/-31.2	8.0/8.0 5.0/9.9	0.37/0.78	AlliedSignal
GABBS, Site 2	38.6192	-118.2300	-1.4/-8.5 -34.9/-38.5	4.7/4.7 5.2/5.7	0.72/0.33	AlliedSignal

Name	Latitude (°)	Longitude ( <sup>o</sup> )	Displacement Power Spectral Density in dB referred to 1 nm²/Hz (Day/Night)  1 Hz	Standard Deviation (Day/Night) 1 Hz 6 Hz	Noise RMS Amplitude (nm) (0.8-3.0 Hz)	Noise Surveyed By
GABBS, Site 3	38.6240	-118.2280	1.9/1.2 -34.9/-33.4	8.9/8.9 6.2/11.5	1.07/0.94	AlliedSignal
GABBS, Site 4	38.6179	-118.2200	-0.8/-5.9 -36.1/-35.8	6.8/4.3 5.3/6.4	0.77/0.42	AlliedSignal
LLNL, Site 1	38.4387	-118.2139	4.2/-8.2 -31.0/-36.5	8.6/12.4 9.7/14.1	0.51/0.32	LLNL
LLNL, Site 3	38.4208	-118.1900	-9.3/-12.9 -32.0/-37.4	9.9/14.5 9.6/14.8	0.33/0.21	LLNL
LLNL, Site 4	38.4150	-118.2106	-4.5/-5.0 -28.9/-30.7	4.7/4.0 6.4/4.8	0.51/0.48	LLNL
LLNL, Site 6	38.4336	-118.2193	-5.2/-5.7 -30.2/-32.3	4.6/4.2 6.2/5.3	0.54/0.52	LLNL
Excelsior Mountains, Site1	38.279	-118.4734	-2.3/-6.0 -33.9/-39.2	7.1/7.1 7.8/9.8	0.65/0.43	LLNL
Excelsior Mountains, Site2	38.2737	-118.4749	-7.4/-8.8 -39.1/-44.3	4.7/3.2 5.8/5.7	0.36/0.31	LLNL
GARA0	38.4268	-118.3000	-8.8/-8.9 -31.0/-33.0	3.7/4.4 4.3/4.6	0.33/0.33	SMU
GARB1	38.4240	-118.3063	-9.6/-9.8 -30.2/-32.5	3.1/3.6 5.3/5.0	0.33/0.32	SMU
GARB2A	38.4208	-118.2898	-9.7/-11.1 -33.7/-37.6	2.3/1.8 7.1/2.0	0.28/0.25	SMU
GARB2	38.4258	-118.2908	-10.8/-11.2 -37.3/-39.3	3.3/3.6 3.8/3.9	0.26/0.25	SMU
GARB3	38.4342	-118.3043	-12.6/-12.3 -40.8/-42.3	2.5/3.0 3.8/3.9	0.21/0.21	SMU
GARBL1	38.4502	-118.2933	-13.5/-13.6 -44.1/-46.5	2.2/2.0 3.5/3.7	0.18/0.18	SMU
GARC4	38.4105	-118.2952	-8.8/-10.0 -35.1/-37.6	4.4/4.9 4.9/5.3	0.30/0.27	SMU

These results can be compared with the United States Geological Survey's (USGS's)

New Low and High Noise Models (NLNM and NHNM) which give -18 and 32 dB re nm<sup>2</sup>/

Hz at 1 Hz, respectively.

With respect to mean PSD values at 1 Hz, GABBS Valleys Site 3 is noisiest with daytime and nighttime noise at +1.9 and +1.2 dB, respectively. Furthermore, the noise levels at sites that are much quieter are LLNL Site 3 east of GAR seismic stations with daytime and nighttime noise levels at -9.3 and -12.9 dB, respectively; and GARB3 with daytime and nighttime noise levels at -12.6 and -12.3 dB, respectively. The site at GARBL1 is the quietest site in this survey with daytime and nighttime noise levels at -13.5 and -13.6 dB, respectively.


With respect to mean PSD values at 6 Hz, daytime noise at MINA Site 3 is noisiest with a value of -25.6 dB. Furthermore, the noise levels at sites that are much quieter at night are MINA Site 4 and LLNL Excelsior Mountains Site 2 with nighttime noise levels at -45.3 and -44.3 dB, respectively. The site at GARBL1 is the quietest site in this survey with daytime and nighttime noise levels at -44.1 and -46.5 dB, respectively.

Signal Coherence Spectra: Signal coherence is excellent with most of coherence values near unity at MINA up to about 2 Hz. Beyond 2 Hz, signal coherency is not interpretable. Good signal coherency is found for other sites such as GABBS, GAR, and LLNL sites. Signal coherency is representable and interpretable at these sites.

Noise Coherence Spectra: Noise coherency is good at GAR and LLNL sites; poorer noise coherency is at MINA and GABBS. Noise coherency is representable and interpretable at these sites.

#### INTRODUCTION

This report is written to record the results of noise spectra obtained from the seismic noise time series acquired in 1997, days 216-224, in the state of Nevada, USA, at MINA seismic stations, GABBS Valleys, Excelsior Mountains, GAR seismic stations, and nearby to the east of GAR seismic stations. The noise surveys at MINA seismic stations and GABBS Valleys were conducted by the AlliedSignal Aerospace/AlliedSignal Technical Services Corp. with four sites at each location. The noise survey to the east of GAR seismic stations composed of four sites and at the Excelsior Mountains (near MINA) composed of two sites were conducted by the Lawrence Livermore National Laboratory (LLNL). The Southern Methodist University (SMU) conducted the noise surveys at the proximity of the existing locations of GAR seismic stations. Figure 1 shows the map indicating the locations of these noise-survey sites. Table 1 lists the locations of these sites.



MAP OF NOISE SURVEY DAYS 216-224 YEAR 1997-WHOLE PART

Figure 1. Site locations of noise survey in Nevada, USA, days 216-224, year 1997.

**Table 1: Site Locations of the Noise Survey** 

SITES	Latitude ( <sup>0</sup> )	Longitude (°)	Surveyed By
MNA1	38.2758	-118.4710	AlliedSignal
MNA2	38.2796	-118.4740	AlliedSignal
MNA3	38.2736	-118.4660	AlliedSignal
MNA4	38.2735	-118.4750	AlliedSignal
GAB1	38.6191	-118.2260	AlliedSignal
GAB2	38.6192	-118.2300	AlliedSignal
GAB3	38.6240	-118.2280	AlliedSignal
GAB4	38.6179	-118.2200	AlliedSignal
LLS1	38.4387	-118.2139	LLNL
LLS3	38.4208	-118.1900	LLNL
LLS4	38.4150	-118.2106	LLNL
LLS6	38.4336	-118.2193	LLNL
EXS1	38.27896	-118.47339	LLNL
EXS2	38.27374	-118.47490	LLNL
GARA0	38.4268	-118.3000	SMU
GARB3	38.4342	-118.3043	SMU
GARB1	38.4240	-118.3063	SMU
GARBL1	38.4502	-118.2933	SMU
GARB2A	38.4208	-118.2898	SMU
GARC4	38.4105	-118.2952	SMU
GARB2	38.4258	-118.2908	SMU

The AlliedSignal Aerospace/AlliedSignal Technical Services Corp. employed the Teledyne Geotech GS-13 seismometer and the RDAS-200P digitizer for their noise survey. LLNL and SMU used the GS-13 and the REFTEK digitizer.

#### **PURPOSE**

The purpose is to investigate the characteristics of noise for site selection in order to set up an International Monitoring System (IMS) station for use under the Comprehensive Test Ban Treaty (CTBT).

#### **INSTRUMENT RESPONSES**

The instrument response of the GS-13/RDAS-200P employed for this noise survey follows that of the Designated Seismic Station (DSS) Vault Seismic System (VSS)<sup>1</sup> [pages 1-6]. The velocity sensitivity is 22.44 counts/nanometers(nm)/second (sec) at 1 Hz for the GS-13/RDAS-200P system for sites surveyed by AlliedSignal. For the GS-13/REFTEK system, the high-gain displacement sensitivity<sup>2</sup> employed at GAR seismic station sites is known as 0.004897 nm/count (or 204.21 counts/nm) at 1 Hz for sites surveyed by SMU; the displacement sensitivity<sup>3</sup> is 844 counts/nm at 4 Hz for sites surveyed by LLNL. In particular, for the instrument response of GS-13/REFTEK system, the assumption has been that the REFTEK digitizer's response is flat at the frequencies of interest. The normalized velocity and displacement amplitude system responses for the GS13/RDAS-200P and GS13/REFTEK, respectively, are shown in Figure 2.


Noise seismograms were corrected for instrument response with the *displacement* system response of the GS13/REFTEK for data provided by the SMU and LLNL groups. The noise ground motion seismograms then become *displacement* noise ground motion seismograms. Noise seismograms which were corrected for the *velocity* system response of the GS13/RDAS-200P for data provided by the AlliedSignal group become *velocity* noise ground motion seismograms. The discussion on what becomes of a ground motion seismogram after an instrument system response correction has been both theoretically treated and exemplified<sup>4</sup>.


<sup>1.</sup> Teledyne Geotech, *Designated Seismic Station (DSS) Vault Seismic System (VSS) - User's Guide*, Document Number 990-59300-9800, Teledyne Geotech, P.O. Box 469007, Garland TX 75046-9007, 1 July 1992.

<sup>2.</sup> Personal communication via e-mail between Paul Golden of SMU and Tom Kelly of CTI dated 3 September 1997.

<sup>3.</sup> Personal communication via e-mail between LLNL and Tom Kelly of CTI dated 3 September 1997.

<sup>4.</sup> Bao V. Nguyen (1995). The instrument responses of the SKM-3 System and the Designated Seismic Station Vault Seismic System, *Bull. Seism. Soc. Am.* **85**, 1835-1846.





**Figure 2**. The normalized velocity and displacement amplitude system responses for the GS13/RDAS-200P and GS13/REFTEK, respectively.

#### **NOISE ANALYSIS**

The individual instrument-corrected noise time series were analyzed employing averaging time domain correlations over a set of data segments after windowing. Subsequently, the average auto-correlation function was Fourier transformed to obtain *power spectral density*. Specifically, an auto-correlation function was computed for each segment of 10 seconds in length and segments were overlapped by 50%. For each segment, the windowing was performed with a *Hanning* windowing function. The collection of windowed auto-correlation functions was then averaged over a set of data segments (windows) and fast Fourier transformed to obtain power spectral density (PSD). In practice, double instrument corrections were performed on the noise power amplitudes after obtaining the auto-correlation function to avoid numerical instability resulting from edge effects of instrument response correction.

From the paragraph above, the *average* and *standard deviation* of power spectral density were computed based on employed noise time series analyzed for each site.

Table 2 lists general information.

**Table 2: General Information** 

Name	Date of Recordings (Year 1997)	Sampling Rate (samples/sec)	Length of Noise Time Series used in PSD (sec)	Measurements made at	Noise Surveyed By
MINA, Site 1	220-223	40	300		AlliedSignal
MINA, Site 2	220-224	40	300		AlliedSignal
MINA, Site 3	220-224	40	300		AlliedSignal
MINA, Site 4	220-224	40	300		AlliedSignal
GABBS, Site 1	228-230	40	300	Open ground, weathered granite	AlliedSignal
GABBS, Site 2	228-230	40	300	Open ground, weathered granite	AlliedSignal

**Table 2: General Information (Continued)** 

Name	Date of Recordings (Year 1997)	Sampling Rate (samples/sec)	Length of Noise Time Series used in PSD (sec)	Measurements made at	Noise Surveyed By
GABBS, Site 3	228-230	40	300	Open ground, weathered granite	AlliedSignal
GABBS, Site 4	228-230	40	300	Open ground, weathered granite	AlliedSignal
LLNL, Site 1	219-223	40	300		LLNL
LLNL, Site 3	219-223	40	300		LLNL
LLNL, Site 4	219-223	40	300		LLNL
LLNL, Site 6	219-223	40	300		LLNL
LLNL, Excelsior Site 1	219-223	40	300		LLNL
LLNL, Excelsior Site 2	219-223	40	300		LLNL
GARA0	216-223	40	300	Lithified conglomerate	SMU
GARB1	216-223	40	300	Lithified conglomerate	SMU
GARB2A	217-218	40	300		SMU
GARB2	218-223	40	300	Alluvium	SMU
GARB3	216-224	40	300	Limestone	SMU
GARBL1	217-223	40	300	Limestone	SMU
GARC4	217-223	40	300	Sandstone	SMU

#### **COMPARISONS**

Since 1993, the United States Geological Survey (USGS) has had a set of new noise models: NLNM (New Low Noise Model) and NHNM (New High Noise Model). These noise models were obtained by graphically fitting straight line segments to the lower and upper envelopes of the spectral overlay of many networks of stations such as the SRO (Seismic Research Observatories) systems, the ASRO systems which are updated versions of the High Gain Long Period (HGLP) seismographs, the Digital World-Wide Standardized Seismograph Network (DWWSSN), the Chinese Digital Seismograph Network (CDSN), the IRIS/USGS (Incorporated Research Institutions for Seismology) systems, the IRIS/IDA (International Deployment of Accelerometers) systems, the Regional Seismic Test Network (RSTN) systems, and TERRAscope systems. In the words of Peterson, "the NLNM is a composite of station spectra obtained from many different instruments, vaults, geologic environments, and geographic regions," and represents "a hypothetical background spectrum that is unlikely to be duplicated at any single location on Earth. The NHNM is a spectrum of average high background noise power in the network. Clearly, one can find sites that are noisier or periods of time at stations in the network that may be affected by microseismic storms or by increased local activities that disturb the instruments." The models plotted in Figures A1-A42 of Appendix A serve as bench marks against which other noise power spectral densities can be compared. At 1 Hz, the NLNM is at -18 dB (referred to displacement power spectral density in 1 nm<sup>2</sup>/Hz); the NHNM is at about 32 dB.


Table 3 lists PSD (Day/Night) comparisons at 1 Hz and 6 Hz for all sites analyzed in this report.

Figures 3a-c show the upper part, middle part, and lower part of the noise survey map as seen from Figure 1 indicating the displacement power spectral density (daytime and nighttime, respectively) at 1 Hz and 6 Hz at these sites.


Figures A1-A42 of Appendix A show noise power spectral densities obtained from these sites.

<sup>1.</sup> Jon Peterson (1993). *Observations and Modeling of Seismic Background Noise*, Open-File Report 93-322, Albuquerque, New Mexico, U.S. Department of Interior Geological Survey.

MAP OF NOISE SURVEY DAYS 216-224 YEAR 1997-UPPER PART



MAP OF NOISE SURVEY DAYS 216-224 YEAR 1997-UPPER PART



**Figure 3a**. Map of noise survey days 216-224 year 1997-upper part-showing PSD values (Day/Night) in dB (re nm<sup>2</sup>/Hz) at 1 Hz and 6 Hz, respectively.

#### MAP OF NOISE SURVEY DAYS 216-224 YEAR 1997-MIDDLE PART

GARB1(-13.5/-13.6) 
$$\triangle$$

GARB3(-12.6/-12.3)  $\triangle$  LLS1(-4.2/-8.2)  $\triangle$  LLS6(-5.2/-5.7)


GARA0(-8.8/-8.9)

GARB1(-9.6/-9.8)  $\triangle$   $\triangle$  GARB2(-10.8/-11.2)  $\triangle$  GARB2A(-9.7/-11.1)

 $\triangle$  LLS3(-9.3/-12.9)  $\triangle$  LLS4(-4.5/-5.0)


GARC4(-8.8/-10.0)

MAP OF NOISE SURVEY DAYS 216-224 YEAR 1997-MIDDLE PART




**Figure 3b**. Map of noise survey days 216-224 year 1997-middle part-showing PSD values (Day/Night) in dB (re nm²/Hz) at 1 Hz and 6 Hz, respectively.

MAP OF NOISE SURVEY DAYS 216-224 YEAR 1997-LOWER PART



MAP OF NOISE SURVEY DAYS 216-224 YEAR 1997-LOWER PART



**Figure 3c.** Map of noise survey days 216-224 year 1997-lower part-showing PSD values (Day/Night) in dB (re nm<sup>2</sup>/Hz) at 1 Hz and 6 Hz, respectively.

Table 3: PSD (Day/Night) Comparisons at 1 Hz and 6 Hz

Name	Displ. PSD in dB re nm <sup>2</sup> /Hz	Standard Deviation	Normalized Noise PSD	Displ. PSD in dB re nm <sup>2</sup> /Hz	Standard Deviation	Normalized Noise PSD	Noise RMS Amplitude (nm)
	(1 Hz)			(6 Hz)			(0.8-3.0 Hz)
NLNM	-18	· -	0.22	-	-	•	=
NHNM	32	-	22380.0	-	-	-	•
Lajitas, Texas <sup>a</sup>	(-11.5) [-9]	-	1.00 1.78	- [-45.16]	<u>-</u>	- 1.00	-
Pinedale <sup>b</sup>	-18.2 [-2.8]	5.7 [12.4]	0.21 7.40	-	-	-	0.16 -
Dubna <sup>c</sup>	-21.5	2.3	0.10		•		0.19
MINA, Site 1	-2.5/-9.0	5.4/5.8	7.94/1.78	-26.7/-32.7	6.3/7.6	70.15/17.62	0.62/0.33
MINA, Site 2	-5.5/-9.2	4.3/4.3	3.98/1.70	-34.7/-40.1	11.1/7.5	11.12/3.21	0.45/0.31
MINA, Site 3	-0.2/-6.8	6.2/6.2	13.49/2.95	-25.6/-32.0	8.2/9.7	90.36/20.70	0.82/0.41
MINA, Site 4	-4.2/-9.5	5.3/5.3	5.37/1.58	-40.5/-45.3	6.5/6.5	2.92/0.97	0.53/0.27
GABBS, Site 1	-7.2/-0.5	8.0/8.0	2.69/12.59	-40.1/-31.2	5.0/9.9	3.21/24.89	0.37/0.78
GABBS, Site 2	-1.4/-8.5	4.7/4.7	10.23/2.00	-34.9/-38.5	5.2/5.7	10.62/4.63	0.72/0.33
GABBS, Site 3	1.9/1.2	8.9/8.9	21.88/18.62	-34.9/-33.4	6.2/11.5	10.62/15.00	1.07/0.94
GABBS, Site 4	-0.8/-5.9	6.8/4.3	11.75/3.63	-36.1/-35.8	5.3/6.4	8.05/8.63	0.77/0.42
LLNL, Site 1	-4.2/-8.2	8.6/12.4	5.37/2.14	-31.0/-36.5	9.7/14.1	26.06/7.35	0.51/0.32
LLNL, Site 3	-9.3/-12.9	9.9/14.5	1.66/0.72	-32.0/-37.4	9.6/14.8	20.70/5.97	0.33/0.21
LLNL, Site 4	-4.5/-5.0	4.7/4.0	5.01/4.47	-28.9/-30.7	6.4/4.8	42.27/27.93	0.51/0.48
LLNL, Site 6	-5.2/-5.7	4.6/4.2	4.27/3.80	-30.2/-32.3	6.2/5.3	31.33/19.32	0.54/0.52
LLNL, Excel- sior Site1	-2.3/-6.0	7.1/7.1	8.32/3.55	-33.9/-39.2	7.8/9.8	13.37/3.94	0.65/0.43
LLNL, Excel- sior Site2	-7.4/-8.8	4.7/3.2	2.57/1.86	-39.1/-44.3	5.8/5.7	4.04/1.22	0.36/0.31
GARA0	-8.8/-8.9	3.7/4.4	1.86/1.82	-31.0/-33.0	4.3/4.6	26.06/16.44	0.33/0.33
GARB1	-9.6/-9.8	3.1/3.6	1.55/1.48	-30.2/-32.5	5.3/5.0	31.33/18.45	0.33/0.32

Table 3: PSD (Day/Night) Comparisons at 1 Hz and 6 Hz (Continued)

Name	Displ. PSD in dB re nm <sup>2</sup> /Hz	Standard Deviation	Normalized Noise PSD	Displ. PSD in dB re nm <sup>2</sup> /Hz	Standard Deviation	Normalized Noise PSD	Noise RMS Amplitude (nm)
	(1 Hz)			(6 Hz)			(0.8-3.0 Hz)
GARB2A	-9.7/-11.1	2.3/1.8	1.51/1.10	-33.7/-37.6	7.1/2.0	14.00/5.70	0.28/0.25
GARB2	-10.8/-11.2	3.3/3.6	1.17/1.07	-37.3/-39.3	3.8/3.9	6.11/3.85	0.26/0.25
GARB3	-12.6/-12.3	2.5/3.0	0.78/0.83	-40.8/-42.3	3.8/3.9	2.73/1.93	0.21/0.21
GARBL1	-13.5/-13.6	2.2/2.0	0.63/0.62	-44.1/-46.5	3.5/3.7	1.28/0.73	0.18/0.18
GARC4	-8.8/-10.0	4.4/4.9	1.86/1.41	-35.1/-37.6	4.9/5.3	10.14/5.70	0.30/0.27

a. Values in parentheses are in dB referred to 1 nm<sup>2</sup>/Hz. Values in brackets are given by Ms. Carol Finn (personal communication) for PSD in dB referred to 1 nm<sup>2</sup>/Hz at 1 Hz for the Pinedale Array noise spectra recorded by the short period instruments model 23900. In addition, for Lajitas, TX, noise spectra were recorded by the TXAR.

#### **COHERENCE ESTIMATES**

Coherence function<sup>1</sup> is a real-valued quantity defined as the ratio of the squared magnitude of the one-sided cross spectrum of the two time series to the product of their one-sided auto spectra and is varied between 0 and 1, inclusive. The coherence function is analogous to the squared correlation coefficient function but is not equal to its Fourier transform. The correlation coefficient function<sup>2</sup> is defined as the ratio of the cross-covariance function of lag time between the two time series to the square root of their product of the auto-covariance functions at zero lag time. The absolute value of the correlation coefficient is less than or equal to 1, inclusive. Mean values different from zero should be removed from the data before computing coherence function to eliminate delta function behavior at the origin<sup>3</sup>.

b. Bao V. Nguyen (1996). Noise power spectral density estimates at Ukrainian site (Makarov), USA site (Pinedale, Wyoming), and Russian sites (Dubna, Peleduy, Ussuriysk, Zalesovo, and near Bilibino), AFTAC, TTR-TN-96-001, 52 pp.

c. Ibid.

<sup>1.</sup> Julius S. Bendat and Allan G. Piersol (1980). *Engineering Applications of Correlation and Spectral Analysis*, John Wiley & Sons, 302 pp.

<sup>2.</sup> Ibid.

<sup>3.</sup> Ibid.

In computing correlation coefficients, the two time series are to be narrow-band passed at each center frequency and the auto- and cross-correlation functions are to be windowed with a window applied to the entire time series length. Normalization is then performed with respect to the maximum amplitude of the auto-correlation function. On the other hand, in computing coherence function in this report, the auto- and cross-correlation functions were windowed with a triangular window applied to each segment, and the segments were overlapped by 65% prior to averaging and Fourier transforming.

Noise is assumed stationary and random; whereas, signal is transient, short in duration, and is assumed to be nonstationary phenomenon with a clearly defined beginning and end. In this report, coherence function is employed for noise coherence estimates from 15-second pre-signal noise time series of each elemental site; whereas, coherence function is employed for signal coherence estimates from 4-second time series for P waves of each elemental site assuming a stochastic process being at work.

Figures B1, B3, B5, B7, and B9 of Appendix B show signal and pre-signal noise coherence as functions of frequency (coherence) and distance (spatial coherence) relative to some reference site. Figures B2, B4, B6, and B8 show spectral multiplications for signals as well as for pre-signal noise of the corresponding elemental sites with some corresponding reference site. These spectral-multiplications figures aid in interpreting the aforementioned coherence estimates of noise and signals of Figures B1, B3, B5, and B7. For example, in Figures B1 and B2 for MINA, excellent signal coherence with values near unity is seen up to about 2 Hz. The signal coherence values drop for frequencies greater than about 2 Hz. But greater than about 2 Hz, the levels of the signal spectral products are about those of the noise spectral products. What can be said of signal coherence estimates for frequencies greater than about 2 Hz at MINA sites is that they are not interpretable. On the other hand, the noise coherence estimates are representable since the noise spectral products exist up to and dropped off at the Nyquist frequency. Similar interpretations can be used to apply to Figures B3 and B4 for GABBS, B5 and B6 for GAR, and B7 and B8 for LLNL sites. Both the signal and noise coherence estimates for GABBS, GAR, and LLNL sites are representable and interpretable up to the Nyquist frequency.

Figure B9 shows spatial coherence varying with distance of elemental sites relative to some reference site evaluated at some representative frequencies. Since only few elemental sites were available, spatial coherency for MINA, GABBS, GAR, and LLNL sites is not meaningful enough for further interpretation and comparison.

#### DISCUSSIONS AND CONCLUSIONS

#### Noise Analysis

The overall results of analysis indicate noise power spectral densities at these sites are low with PSD values ranging from +1.9 to -13.6 dB re nm<sup>2</sup>/Hz at 1 Hz and from -25.6 to -46.5 dB at 6 Hz.

Low amplification of noise is seen at 3.5 Hz, 9 Hz, and 16 Hz at MINA Site 2; 2.0 Hz, 3.5 Hz, and 8.5 Hz at MINA Site 4.

Low amplification of noise is seen for GABBS Valley Sites 1 and 3 at 16 Hz; 8 Hz at Site 3 for mostly nighttime; 8 Hz and 15 Hz at Site 2 for nighttime; 3.5 Hz and 4.0 Hz at Site 4.

Low amplification of noise is seen for LLNL Site 6 at 16 Hz; 3.5 Hz and 4.0 Hz at Sites 1, 3, and 6; 3.5 Hz at Site 4; 8 Hz at Site 1; 9 Hz at Site 6.

Low amplification of noise is seen for LLNL Excelsior Mountains Sites 1 and 2 (near MINA) at 3.5 Hz; 8 Hz at Site 2; 9.5 Hz at Site 1; 12 Hz at Site 2.

Low amplification of noise is seen for SMU GAR Sites A0, B1, B2, B2A, B3, BL1, and C4 at 3.5 Hz; 4.0 Hz at A0, B2, BL1, and C4; 8 Hz at A0, B1, B2, B2A, BL1, and C4; 12 Hz at A0, B1 and B2.

With respect to mean PSD values at 1 Hz, GABBS Valleys Site 3 is noisiest with daytime and nighttime noise at +1.9 and +1.2 dB, respectively. Furthermore, the noise levels at

sites that are much quieter are LLNL Site 3 east of GAR seismic stations with daytime and nighttime noise levels at -9.3 and -12.9 dB, respectively; GARB3 with daytime and nighttime noise levels at -12.6 and -12.3 dB, respectively. The site at GARBL1 is the quietest site in this survey with daytime and nighttime noise levels at -13.5 and -13.6 dB, respectively.


With respect to mean PSD values at 6 Hz, daytime noise at MINA Site 3 is noisiest with a value of -25.6 dB. Furthermore, the noise levels at sites that are much quieter at night are MINA Site 4 and LLNL Excelsior Mountains Site 2 with nighttime noise levels at -45.3 and -44.3 dB, respectively. The site at GARBL1 is the quietest site in this survey with daytime and nighttime noise levels at -44.1 and -46.5 dB, respectively.

Figure 4 shows a composite of noise levels at 1 Hz and 6 Hz for all the sites of this noise survey.

#### Coherence Analysis

Signal Coherence Spectra: Signal coherence is excellent with most of coherence values near unity at MINA up to about 2 Hz. Beyond 2 Hz, signal coherency is not interpretable. Good signal coherency is found for other sites such as GABBS, GAR, and LLNL sites. Signal coherency is representable and interpretable at these sites.

Noise Coherence Spectra: Noise coherency is good at GAR and LLNL sites; poorer noise coherency is at MINA and GABBS. Noise coherency is representable and interpretable at these sites.




**Figure 4**. A composite of mean noise levels (day and night) at 1 Hz and 6 Hz for all the sites of this noise survey.


#### **REFERENCES**

- Bendat, Julius S., and Allan G. Piersol (1980). Engineering Applications of Correlation and Spectral Analysis, John Wiley & Sons, 302 pp.
- Nguyen, Bao V. (1995). The instrument responses of the SKM-3 System and the Designated Seismic Station Vault Seismic System, *Bull. Seism. Soc. Am.* **85**, 1835-1846.
- Nguyen, Bao V. (1996). Noise power spectral density estimates at Ukrainian site (Makarov), USA site (Pinedale, Wyoming), and Russian sites (Dubna, Peleduy, Ussuriysk, Zalesovo, and near Bilibino), AFTAC, TTR-TN-96-001, 52 pp.
- Peterson, Jon (1993). Observations and Modeling of Seismic Background Noise, Open-File Report 93-322, Albuquerque, New Mexico, US Department of Interior Geological Survey.
- Teledyne Geotech, *Designated Seismic Station (DSS) Vault Seismic System (VSS) User's Guide*, **Document Number 990-59300-9800**, Teledyne Geotech, P.O. Box 469007, Garland TX 75046-9007, 1 July 1992.


## APPENDIX A: PLOTS OF DISPLACEMENT POWER SPECTRAL DENSITY




**Figure A1**. Daytime mean noise PSD at Mina Site 1. There are N=18 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A2**. Nighttime mean noise PSD at Mina Site 1. There are N=13 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A3**. Daytime mean noise PSD at Mina Site 2. There are N=23 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A4**. Nighttime mean noise PSD at Mina Site 2. There are N=22 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A5**. Daytime mean noise PSD at Mina Site 3. There are N=19 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A6**. Nighttime mean noise PSD at Mina Site 3. There are N=25 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A7**. Daytime mean noise PSD at Mina Site 4. There are N=20 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A8**. Nighttime mean noise PSD at Mina Site 4. There are N=25 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A9.** Daytime mean noise PSD at Gabbs Site 1. There are N=10 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A10**. Nighttime mean noise PSD at Gabbs Site 1. There are N=13 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A11**. Daytime mean noise PSD at Gabbs Site 2. There are N=10 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A12**. Nighttime mean noise PSD at Gabbs Site 2. There are N=12 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A13**. Daytime mean noise PSD at Gabbs Site 3. There are N=6 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A14**. Nighttime mean noise PSD at Gabbs Site 3. There are N=12 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A15**. Daytime mean noise PSD at Gabbs Site 4. There are N=10 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A16**. Nighttime mean noise PSD at Gabbs Site 4. There are N=12 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A17**. Daytime mean noise PSD at LLNL Site 1 (east of GAR). There are N=110 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A18**. Nighttime mean noise PSD at LLNL Site 1 (east of GAR). There are N=130 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A19**. Daytime mean noise PSD at LLNL Site 3 (east of GAR). There are N=108 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A20**. Nighttime mean noise PSD at LLNL Site 3 (east of GAR). There are N=130 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A21**. Daytime mean noise PSD at LLNL Site 4 (east of GAR). There are N=110 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A22**. Nighttime mean noise PSD at LLNL Site 4 (east of GAR). There are N=130 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A23**. Daytime mean noise PSD at LLNL Site 6 (east of GAR). There are N=110 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A24**. Nighttime mean noise PSD at LLNL Site 6 (east of GAR). There are N=130 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A25**. Daytime mean noise PSD at LLNL Excelsior Mountains Site 1. There are N=110 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A26**. Nighttime mean noise PSD at LLNL Excelsior Mountains Site 1. There are N=130 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A27.** Daytime mean noise PSD at LLNL Excelsior Mountains Site 2. There are N=110 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A28**. Nighttime mean noise PSD at LLNL Excelsior Mountains Site 2. There are N=128 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A29.** Daytime mean noise PSD at SMU GARA0 seismic station. There are N=83 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A30**. Nighttime mean noise PSD at SMU GARA0 seismic station. There are N=91 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A31**. Daytime mean noise PSD at SMU GARB1 seismic station. There are N=78 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A32**. Nighttime mean noise PSD at SMU GARB1 seismic station. There are N=91 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A33**. Daytime mean noise PSD at SMU GARB2 seismic station. There are N=69 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A34**. Nighttime mean noise PSD at SMU GARB2 seismic station. There are N=78 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A35**. Daytime mean noise PSD at SMU GARB2A seismic station. There are N=6 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A36**. Nighttime mean noise PSD at SMU GARB2A seismic station. There are N=13 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A37**. Daytime mean noise PSD at SMU GARB3 seismic station. There are N=89 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A38**. Nighttime mean noise PSD at SMU GARB3 seismic station. There are N=104 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A39.** Daytime mean noise PSD at SMU GARBL1 seismic station. There are N=72 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.



**Figure A40**. Nighttime mean noise PSD at SMU GARBL1 seismic station. There are N=78 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A41**. Daytime mean noise PSD at SMU GARC4 seismic station. There are N=67 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.




**Figure A42**. Nighttime mean noise PSD at SMU GARC4 seismic station. There are N=78 time series of noise samples. Each time series has a length L=300 seconds and is segmented by segments of SEGMT=10 seconds. Segments were overlapped by OVL=50%.


## APPENDIX B: PLOTS OF SIGNAL AND NOISE COHERENCE SPECTRA




**Figure B1**. (a) Signals (P waves) recorded at MINA sites. (b) Signal correlation functions relative to site 4. (c) Pre-signal noise at four sites. (d) Noise correlation functions relative to site 4. (e-g) Signal and noise coherency of sites 1, 2, and 3, relative to site 4.




**Figure B2**. Spectral multiplications for signals as well as for pre-signal noise of sites 1, 2, and 3, with site 4.




**Figure B3**. (a) Signals (P waves) recorded at GABBS sites. (b) Signal correlation functions relative to site 2. (c) Pre-signal noise at three sites. (d) Noise correlation functions relative to site 2. (e-f) Signal and noise coherency of sites 1 and 4, relative to site 2.




**Figure B4**. Spectral multiplications for signals as well as for pre-signal noise of sites 1 and 4, with site 2.




**Figure B5**. (a) Signals (P waves) recorded at GAR sites. (b) Signal correlation functions relative to site B3. (c) Pre-signal noise at three sites. (d) Noise correlation functions relative to site B3. (e-f) Signal and noise coherency of sites BL1 and C4, relative to site B3.




**Figure B6**. Spectral multiplications for signals as well as for pre-signal noise of sites BL1 and C4, with site B3.



**Figure B7**. (a) Signals (P waves) recorded at LLNL sites. (b) Signal correlation functions relative to site 4. (c) Pre-signal noise at four sites. (d) Noise correlation functions relative to site 4. (e-g) Signal and noise coherency of sites 1, 3, and 6, relative to site 4.



**Figure B8**. Spectral multiplications for signals as well as for pre-signal noise of sites 1, 3, and 6, with site 4.



**Figure B9**. Spatial coherency as function of distance at some representative frequencies for signals (solid) and noise (dashed) at MINA, GABBS, LLNL, and GAR sites.

## **DISTRIBUTION**

California Institute of Technology ATTN: Prof. Thomas Ahrens Seismological Laboratory, 252-21 Pasadena CA 91125

Air Force Research Laboratory ATTN: Research Library/TL 5 Wright St. Hanscom AFB MA 01731-3004

Air Force Research Laboratory ATTN: VSOE 29 Randolph Rd. Hanscom AFB MA 01731-3010

Air Force Research Laboratory ATTN: AFRL/SUL 3550 Aberdeen Ave., SE Kirtland AFB NM 87117-5776

NTPO ATTN: Dr. R.W. Alewine 1901 N. Moore Street, Suite 609 Arlington VA 22209

Pennsylvania State University ATTN: Prof. S. Alexander & Prof. C.A. Langston Department of Geosciences 537 Deike Building University Park PA 16802

University of Colorado
ATTN: Prof. C. Archambeau, Prof. D. Harvey,
Dr. Anatoli Levshin, & Prof. M. Ritzwoller
Department of Physics
Campus Box 583
Boulder CO 80309-0583

Science Application International Corporation ATTN: Dr. T. Bache, Jr. & Dr. T.J. Sereno 10260 Campus Point Drive San Diego CA 92121-1578

Center for Monitoring Research ATTN: Librarian 1300 N. 17th St., Suite 1450 Arlington VA 22209

Cornell University
ATTN: Prof. M. Barazangi
Institute for the Study of the Continents
Department of Geological Sciences
3126 SNEE Hall
Ithaca NY 14853

State University of New York, Binghamton ATTN: Prof. F.T. Wu
Department of Geological Sciences
Binghamton NY 13901

Maxwell Technologies ATTN: Dr. T.G. Barker & Dr. J. Stevens 8888 Balboa Ave. San Diego CA 92123-1506

ENSCO, Inc./APA Division ATTN: Dr. D.R. Baumgardt & Dr. Z. Der 5400 Port Royal Road Springfield VA 22151-2388

University of Arizona ATTN: Dr. S. Beck & Prof. T.C. Wallace Department of Geosciences Gould Simpson Building Tuscon AZ 85721

Maxwell Technologies ATTN: Dr. T.J. Bennett & Mr. J. Murphy Geophysics & Resource Technologies Group 11800 Sunrise Valley Drive, Suite 1212 Reston VA 22091

University of California, San Diego ATTN: Dr. J. Berger, Dr. L. Burdick, Dr. H. Given, Dr. M. Hedlin, Prof. B. Minster, Prof. J.A. Orcutt, & Dr. F.L. Vernon Scripps Institution of Oceanography IGPP, 0225 9500 Gilman Dr. La Jolla CA 92093-0255 Schlumberger-Doll Research Center ATTN: Dr. R. Burridge

Old Quarry Road Ridgefield CT 06877

Department of Energy ATTN: Ms. Leslie A. Casey Office of R&D, NN-20 1000 Independence Ave., SW Washington DC 20585-0420

Virginia Polytechnical Institute ATTN: Dr. M. Chapman Seismological Observatory Department of Geological Sciences 4044 Derring Hall Blacksburg VA 24061-0420

Arms Control & Disarmament Agency ACDA/IVI/VC ATTN: Mr. R. Cockerham & Mr. R. Morrow 320 21st Street N.W. Washington DC 20451

University of Connecticut, Storrs ATTN: Prof. V.F. Cormier Department of Geology & Geophysics U-45, Room 207 Storrs CT 06269-2045

HQ DSWA/PMA ATTN: Dr. Anton Dainty 6801 Telegraph Rd. Alexandria VA 22310-3398

San Diego State University ATTN: Dr. S. Day Department of Geological Sciences San Diego CA 92182

Defense Technical Information Center 8725 John J. Kingman Road, Suite 0944 Ft. Belvoir VA 22060-6218 University of California, San Diego ATTN: Dr. Catherine de Groot-Hedlin Institute of Geophysics & Planetary Sciences 8604 La Jolla Shores Drive San Diego CA 92093

University of Texas, El Paso ATTN: Ms. Diane Doser Department of Geological Sciences El Paso TX 79968

Harvard University
ATTN: Prof. A. Dziewonski
Hoffman Laboratory
Department of Earth, Atmospheric &
Planetary Sciences
20 Oxford Street
Cambridge MA 02138

Boston College ATTN: Prof. J. Ebel & Prof. A. Kafka Department of Geology & Geophysics Chestnut Hill MA 02167

Mission Research Corporation ATTN: Dr. M. Fisk & Dr. W. Wortman 8560 Cinderbed Rd., Suite 700 Newington VA 22122

Brown University
ATTN: Prof. D. Forsyth
Department of Geological Sciences
Providence RI 02912

Defense Intelligence Agency/PAG-1A ATTN: Dr. D.P. Glover Washington DC 20340-6160

Multimax, Inc. ATTN: Ms. Lori Grant 311C Forest Ave., Suite 3 Pacific Grove CA 93950 Southern Methodist University ATTN: Dr. Henry Gray Department of Statistics P.O. Box 750302 Dallas TX 75275-0302

Multimax, Inc. ATTN: Dr. I.N. Gupta & Mr. W. Rivers 1441 McCormick Drive Largo MD 20774

Pacific Northwest National Laboratories ATTN: Mr. D.N. Hagedorn P.O. Box 999, MS F5-12 Richland WA 99352

Lawrence Livermore National Laboratory ATTN: Dr. J. Hannon & Dr. K. Nakanishi P.O. Box 808, L-205 Livermore CA 94550

MIT ERL E34-404 ATTN: Dr. David Harkrider 42 Carlton St. Cambridge MA 02142-1324

New Mexico State University ATTN: Prof. Thomas Hearn & Prof. James Ni Department of Physics Las Cruces NM 88003

California Institute of Technology ATTN: Dr. Donald Helmberger Division of Geological & Planetary Sciences Seismological Laboratory Pasadena CA 91125

Southern Methodist University ATTN: Dr. E. Herrin & Dr. B. Stump Department of Geological Sciences P.O. Box 750395 Dallas TX 75275-0395 St. Louis University
ATTN: Prof. R. Herrmann & Prof. B. Mitchell
Department of Earth & Atmospheric Sciences
3507 Laclede Ave.
St. Louis MO 63103

HQ DSWA/PMP/CTBT ATTN: Dr. M. Shore & Mr. Rong-Song Jih 6801 Telegraph Rd. Alexandria VA 22310-3398

University of California, Berkeley ATTN: Prof. L.R. Johnson & Prof. T. McEvilly Earth Sciences Division LBNL 90-2106, MS 90-1116 479 McCone Hall Berkeley CA 94720

Massachusetts Institute of Technology ATTN: Prof. T.H. Jordan Department of Earth, Atmospheric & Planetary Sciences 77 Massachusetts Ave., 654-918 Cambridge MA 02139

Massachusetts Institute of Technology ATTN: Dr. R. LaCross, M-200B Lincoln Laboratory P.O. Box 73 Lexington MA 02173-0073

University of Illinois, Urbana-Champaign ATTN: Prof. F.K. Lamb & Prof. J. Sullivan Department of Physics 1110 West Green Street Urbana IL 61801

Oklahoma Geological Survey Observatory ATTN: Dr. J. Lawson, Chief Geophysicist P.O. Box 8 Leonard OK 74043-0008 University of California, Santa Cruz

ATTN: Dr. T. Lay, Dr. S. Schwartz, & Dr. R. Wu ATTN: Dr. A. McGarr

Earth Sciences Dept.

Earth & Marine Sciences Building

Santa Cruz CA 95064

US Geological Survey ATTN: Dr. W. Leith 920 National Center Reston VA 22092

Weston Geophysical Corp.
ATTN: Mr. James Lewkowicz

325 West Main St. Northboro MA 01532

ACDA/VI-OA

ATTN: Mr. A Lieberman

State Department Building, Room 5726

320 21st Street, NW Washington DC 20451

AFTAC/CA(STINFO)/TT/TTR/TTD

1030 South Highway A1A Patrick AFB FL 32925-3002

Georgia Institute of Technology

ATTN: Prof. L.T. Long

School of Geophysical Sciences

Atlanta G 30332

US Geological Survey

ATTN: Dr. R. Masse

Denver Federal Building

Box 25046, Mail Stop 907

Denver CO 80225

Southern Methodist University

ATTN: Dr. G. McCartor

Department of Physics

P.O. Box 750175

Dallas TX 75275-0175

US Geological Survey ATTN: Dr. A. McGarr National Earthquake Center

345 Middlefield Rd., MS-977

Menlo Park CA 94025

Center for Monitoring Research

ATTN: Dr. K.L. McLaughlin & Dr. R. North

1300 North 17th Street Arlington VA 22209-3871

Office of the Secretary of Defense

DDR&E

Washington DC 20330

Yale University

ATTN: Prof. J. Park

Department of Geology & Geophysics

P.O. Box 208109

New Haven CT 06520-8109

University of Cambridge

ATTN: Prof. Keith Priestly

Bullard Labs, Department of Earth Sciences

Madingley Rise, Madingley Road

Cambridge CB3 OEZ, UNITED KINGDOM

BBN Systems & Technologies

ATTN: Dr. J.J. Pulli

1300 N. 17th St., Suite 1200

Arlington VA 22209

Defense Special Weapons Agency

ATTN: Dr. R. Reinke, FCDNA/FCTTS

1680 Texas S., SE

Kirtland AFB NM 87117-5669

**DTR** Associates

ATTN: Dr. Delaine Reiter

73 Standish Rd.

Watertown MA 02172

Columbia University

ATTN: Prof. P. Richards & Dr. J. Xie

Lamont-Doherty Geological Observatory

Route 9W

Palisades NY 10964

Woodward-Clyde Federal Services ATTN: Dr. C.K. Saikia 566 El Dorado Street, Suite 100 Pasadena CA 91101-2560

University of Southern California, Los Angeles ATTN: Prof. C.G. Sammis Center for Earth Sciences University Park Los Angeles CA 90089-0741

Secretary of the Air Force (SAFRD)
Washington DC 20330

University of California, Davis ATTN: Dr. R. Shumway Division of Statistics 410 MRAK Hall Davis CA 95616-8671

AFOSR/NL 110 Duncan Avenue Bolling AFB Washington DC 20332-0001

Los Alamos National Laboratory
ATTN: Dr. H. Patton, Dr. S.R. Taylor,
Dr. Jill Warren, & Dr. T. Weaver
Geophysics Group EES-3, MS C335
P.O. Box 1663
Los Alamos NM 87545

Massachusetts Institute of Technology ATTN: Prof. M.N. Toksoz Earth Resources Lab, 34-440 42 Carleton Street

42 Carleton Street
Cambridge MA 02142

ACIS ATTN: Dr. L. Turnbull New Headquarters Bldg., Room 4W03 Washington DC 20505 National Science Foundation ATTN: Dr. Daniel Weill Division of Earth Sciences, EAR-785 4201 Wilson Blvd., Room 785 Arlington VA 22230

I.R.I.G.M. - B.P. 68 ATTN: Dr. Michel Bouchon 38402 St. Martin D'Heres Cedex, FRANCE

I.R.I.G.M. - B.P. 53 ATTN: Dr. Michel Campillo Observatorie de Grenoble 38041 Grenoble, FRANCE

Ruhr University, Bochum
ATTN: Prof. Hans-Peter Harjes &
Dr. Johannes Schweitzer
Institute for Geophysics
P.O. Box 102148
W-4630 Bochum 1, GERMANY

NTNF/NORSAR ATTN: Dr. Svein Mykkeltveit P.O. Box 51 N-2007 Kjeller, NORWAY

Bureau of Mineral Resources
ATTN: Mr. David Jepsen, Acting Head,
Nuclear Monitoring Section
Geology and Geophysics
G.P.O. Box 378
Canberra, ACT 2601, AUSTRALIA

Atomic Weapons Establishment ATTN: Dr. P. Marshall Blacknest, Brimpton Reading FG7 4RS, UNITED KINGDOM

Societe Radiomana
ATTN: Dr. Bernard Massinon &
Dr. Pierre Mechler
27 rue Claude Bernard
75005 Paris, FRANCE

University of Bergen ATTN: Prof. Eystein Husebye Institute for Solid Earth Physics Allegaten 40 N-5007, Bergen, NORWAY